

KERN BFA600K-1SNM

Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	600 g
Load cell connection:	4-wire
Number of weighing ranges:	1
Readability [d]:	200 g
Recommended adjusting weight:	600 kg (M2)
Repeatability:	200 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-600 kg
Warm up time:	10 min
Weighing capacity [Max]:	600 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height (large):	5,200 cm
Technical data about verification	
Minimum load [Min]:	4 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	200 g

Functions

Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal	yes
weighing program):	

display device (IP65), with EC type appro	vartivij	
Weighing with tolerance range:	yes	
Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0%	
Miniman namiaty.	0 /0	
Power supply		
Battery:	no battery	
Charging time:	12 h	
Input voltage:	100 V - 240 V 50 / 60 Hz	
Mains adapter:	Mains adapter external	
Mains adapter/adapter included:	EURO CH UK US	
Operating time (Backlight off):	35 h	
Operating time (Backlight on):	20 h	
Services (optional)		
Adjustment at the location of installation: 961-250		
DAkkS Certificate:	963-130	
Verification:	965-230	
Category		
Brand:	KERN	
Category:	Balances	
Product Group:	Floor scale	
Packaging & shipping		
Delivery:	120 h	
Dimensions packaging (WxDxH):	1120 x 1080 x 220 mm	
Gross weight:	130 kg	
Net weight:	105 kg	
Shipping method:	Freight forwarder	
UN number:	2800	
Construction		
Cable length:	5 m	
Cable length of display device:	5 m	
Dimensions of display device	266 x 165 x 96 mm	
(WxDxH):		
Dimensions of weighing plate (WxDxH):	1000 x 1000 x 85 mm	
Level indicator:	yes	
Revolving screw feet:	yes	
Wall mount:	yes	
Weighing surface (WxD):	1000 x 1000 mm	

ICS Schneider Messtechnik GmbH Briesestraße 59 D-16562 Hohen Neuendorf / OT Bergfelde

Tel.: 03303 / 504066 Fax: 03303 / 504068 info@ics-schneider.de www.ics-schneider.de

KERN BFA600K-1SNM

Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]

Piktogramme STANDARD M B 1 . H^ 666 666 ---· 30 TOL MOVE IP65 IP67 MULTI DMS CAL EXT PCS SUM 2 DAYS OPTION DAkkS +3 DAYS FACTORY

