



# PV624

## Portable hybrid pressure controller

### GENii Advanced Modular Calibration System

The PV624 is a portable hybrid pressure controller base station that combines the advantages of manual pressure generation with fully automatic pressure generation and control.

Using the PV624 with a DPI620G electrical calibrator and interchangeable PM620/PM620T pressure modules from the GENii advanced modular calibration system creates a uniquely capable, flexible, self-contained portable hybrid pressure controller.

The PV624 hybrid pressure controller offers an easy and fast method to accurately maintain pressure set points. Hybrid pressure control also supports large test volumes and long battery life.

With a robust design and tool-less pressure connection, the PV624 is ideally suited to perform pressure testing and calibrations in the field.

### Features

- In-the-field pressure range selection from the GENii PM620/PM620T pressure module family.
- In built barometer to enable accurate pseudo pressure measurements.
- Hybrid pressure generation and control from -0.9barg (-13psig) to 20barg (300psig).
- Automatic selection of manual pressure generation, automatic pressure generation or pressure venting with large test volume capability.
- Fully automatic pressure generation and control to accurately maintain setpoint.
- Minimise in-the-field leaks with quick-fit pressure adapters.
- Physical or \*Bluetooth® wireless connection to a DPI620G electrical calibrator.
- In-the-field rechargeable battery pack replacement.
- Autonomous calibration wizard to store procedures and calibration data.

## Druck PV624 portable hybrid pressure controller

The PV624 automatically selects between fast high volume manual pressure generation and fully automatic precise pressure generation to quickly achieve and accurately maintain a stable setpoint.

To achieve a fast time to up-scale pressure set points (or down-scale pressure set points for negative pressure ranges), the hand pump is requested by the PV624 to be exercised for a portion of the pressure change before automatically isolating the hand pump and seamlessly engaging fully automatic pressure generation to set point.

Down-scale pressure set points (or up-scale pressure set points for negative pressure ranges) are quickly achieved with automatically controlled venting.

Once at set point the PV624 automatically generates and controls the pressure to combat the effect of adiabatic or minor leaks.



## Modular Integration

The PV624 portable hybrid pressure controller connects physically or \*wirelessly via Bluetooth® with any Bluetooth® \*\*DPI620G electrical calibrator.

A simple hand tight screw fit (no tools required) makes both an electrical and pressure connection to a range of fully interchangeable \*\*PM620/PM620T pressure modules.

By utilizing the PV624 internal barometer, a PM620 pressure module reference type can be changed by the user from gauge to \*\*\*pseudo absolute or from absolute to \*\*\*pseudo gauge.



## Precision engineering

The choice of case material and precision over moulding ensures that the PV624 is rugged, weatherproof, and suitable for the harshest environments.

Supplied with a dirt trap to reduce contamination of both the instrument itself and the system under test from dirt and debris as well as moisture.

## Ease of Use

The PV624 provides a tool-less quick-fit pressure connection where finger-tight connections achieve pressure-tight connections to 20 bar. Supplied with a G1/8 female and 1/8 NPT female adapter (other adapters available, see accessories).

The PV624 is supplied with an AC adapter and a rechargeable battery pack that can be charged in the unit, or is easily exchanged in the field with a charged additional battery (additional battery and external charger available as an accessory).

\*Due to individual country radio licence requirements, Bluetooth® wireless technology may not be available in some countries. An up-to-date list of countries where with Bluetooth® wireless technology is licenced to be used in is available upon request from Druck. User will also need a Bluetooth® Genii & Bluetooth® PV624 to allow this.

\*\*The PV624 is not compatible with any hazardous area intrinsically safe approved products e.g.DPI620-IS or PM620-IS

\*\*\*pseudo selection only available for PM620 1 bar/15psi gauge full-scale ranges or above and for 2bar/30psi absolute full-scale ranges and above

Druck PV600 series portable pressure base stations

The PV624 is a portable hybrid pressure controller base station that joins the GENii advanced modular calibration system. The unique hybrid pressure generation and control technology compliments the established PV621/622/623 manual pressure generation and control base stations offering pressure generation from vacuum to 100 bar (1,500 psi) pneumatic and up to 1,000 bar (15,000 psi) hydraulic.



GENii Advanced Modular Calibration system

The Druck GENii advanced modular calibration system comprises of four possible system components to provide the multifunctionality to perform duties formerly requiring a wide range of different instruments. These system components are:

- DPI620G – Electrical/Multi-function calibrator, HART/Fieldbus communicator
- PM620/PM620T – Interchangeable pressure modules (–all ranges from 0.7bar/10psi up to 20 bar/300 psi compatible with the PV624)
- MC620G – Pressure module carrier
- PV62XG (including the PV624) – Pressure generating base stations.



This user selectable flexible system allows the choice of multiple DPI620G models to be used as a standalone electrical/multi-function calibrator, as a pressure reference with the addition of a pressure module carrier and pressure modules or as a self-contained pressure calibrator with a pressure base station and a pressure module.

Calibration procedures

Test procedures can be created and stored using the autonomous “Calibration Wizard”. A single test procedure template can be run on multiple devices with live pass/fail error analysis and results for each device saved individually in the internal storage of the DPI620G that can be locally viewed or transferred to a PC to support traceability.

With the test results exported to a PC, the data can be sorted or Druck provides a Calibration Certificate template for pressure to electrical device calibrations, which transforms the results into a formatted professional-look certificate ready for printing or filing.

The PV624 is also compatible with Druck’s 4Sight2 calibration management software that provides full visibility of all your assets and reference standards with calibration workload scheduling, track and trace calibrations, historical trending and drift analysis features to drive process efficiency and time saving.

Druck Ltd  
2 Fir Tree Lane, LE60FH

Calibration Certificate

DEVICE UNDER TEST		CALIBRATION	
Device Identifier	PS12145	Calibration Date	4/24/2023 14:34:1 PM
Serial Number	235	User	Tech01
Manufacturer	Druck	Location	location
Model	Unik5000	Ambient Temperature	20 °C
Sensor Type	Gauge	Ambient Pressure	981.02 mbar
		Ambient Humidity	70%

TEST EQUIPMENT		ADDITIONAL SENSORS 2	
MAIN CALIBRATOR		Manufacturer	Druck
LOCATION		Model	PM620-10G
Manufacturer	Druck	Serial Number	12281613
Model	DPI620	Calibration Date	07-Jul-22
Serial Number	5255729	Sensor Type	Gauge
Calibration Date	27-Oct-22	Range	-1 to 7 Bar
Manufacturer		Druck	
Model		PV624	
Serial Number		124225658	
Calibration Date		28-Feb-23	
Sensor Type		Abs	
Range		800 to 1100 mbar	

RANGE		TOLERANCE	
Input	0 To 2 bar gauge	Test Point	5%
Output	4 To 20 mA	Pass/Fail	5 % Span
Relationship	Linearity	Adjustment	3 % Span

As Found

Result: Pass						
#	Expected Input	Actual Input	Expected Output	Actual Output	Error	Status
	P1	P1	CH2	CH2		
	bar	bar	mA	mA	mA	
1	0	-0.0006	4.0000	3.9900	0.0100	Pass
2	0.5	0.4900	8.0000	7.9900	0.0100	Pass
3	1	0.9900	12.0000	11.9800	0.0200	Pass
4	1.5	1.5500	16.0000	15.9500	0.0500	Pass
5	2	2.0000	20.0000	19.9500	0.0500	Pass

## Specifications

### Range and Performance

#### Hybrid pressure control range

-0.9 barg (-13 psig) to 20 barg (300 psig)

#### Compatible PM620 & PM620T (FS) pressure ranges

Gauge ranges: 0.7 barg (10 psi), 1 barg (15 psi), 2 barg (30 psi), 3.5 barg (50 psi), 7 barg (100 psi), 10 barg (150 psi), 20 barg (300 psi).

Absolute ranges: 2 barg (30 psi), 3.5 barg (50 psi), 7 barg (100 psi), 10 barg (150 psi), 20 barg (300 psi).

#### Maximum over range pressure (without damage)

120%FS

#### Barometer pressure measurement range

800-1100 mbar abs

#### Barometer total uncertainty (24hr)

<0.5 mbar

#### Barometer drift/year

<0.33 mbar/yr typical

#### Pressure control stability

50 ppm of PM620 Full Scale

#### Speed to stable set point

0 barg to 2 barg (30 psig) +/-50 ppm into 15 ml volume <15 sec

0 barg to 20 barg (300 psig) +/-50 ppm into 50 ml volume <90 sec

#### Maximum compensated leak rate at 20 barg (300 psig) with 50 mL volume

60 mbar/min



## General Specification

#### Operating temperature

0 to +50 deg. C

#### Storage temperature

-20 to +70 deg. C

#### Ingress protection

IP54

#### Humidity

Up to 95% non-condensing

#### Shock/vibration

As per MIL-PRF-28800F (Class II equipment)

#### Altitude

Up to 3000m

#### EMC:

CE and UKCA approved IEC61326-1

#### Electrical safety:

CE and UKCA approved IEC61010

#### Pressure safety:

CE and UKCA approved Sound Engineering Practice

#### Test volume materials

Suitable for air

#### Approvals

CE marked, UKCA marked

#### Size (excl DPI620)

(L) 343mm/13.5" x (W) 192mm/7.6" x (H) 136mm/5.4"

#### Weight (excl DPI620)

3.4Kg/7.5lb

#### Power supply

15V, 2A (30W)

#### Battery life (from 100% charge)

Min 8hrs continuous usage (typical)

#### Battery charge time

8hrs

#### Service

>5000 pressure cycles

#### Power failure protection

System lock and manual vent valve feature provided

#### Connectivity

USB client micro-USB (+Bluetooth® low energy for B1 option)

#### Pressure connection

Quick fit with G1/8 female + 1/8 NPT female adapter



## Ordering information for the PV624

### Model type

**PV624** Hybrid Pressure Controller Base Station

### Connectivity to DPI620

B0 Standard electrical connection

B1 Standard electrical connection plus \*Bluetooth\*

**PV624 – B0 (Example model number)**



## Standard specification

- 1x PV624 Hybrid pressure controller base station
- 1x Shoulder/carry strap
- 1x AC power supply
- 1x Rechargeable battery pack
- 1x Quick start/safety manual
- 1x G1/8 female adapter
- 1x 1/8 NPT female adapter
- 1x Dirt moisture trap

## Accessories for the PV624

### Pressure station carrying case

A protective carrying case with shoulder strap and large pocket for accessories. Also accommodates the assembled system including the DPI620 and PM620. P/N IO620-CASE-3.



### Power

A spare rechargeable battery pack P/N IO624-Battery

An external desktop battery charger for the PV624 battery pack:

- UK Plug – P/N IO624-CHGR-KIT-UK
- European Plug – P/N IO624-CHGR-KIT-EU
- USA Plug – P/N IO624-CHGR-KIT-US
- Australia Plug – P/N IO624-CHGR-KIT-AU

### Pneumatic hoses

A pneumatic hose rated to 35 bar (508 psi). The hose connects directly to the PV624 pressure port and replicates the quick fit connection for compatibility with the standard adaptors supplied and the adaptor kits.

**P/N IOHOSE-NP1:** 1m/3.28ft pneumatic hose kit

**P/N IOHOSE-NP2:** 2m/6.56ft pneumatic hose kit

**P/N IOHOSE-NP3:** 3m/9.84ft pneumatic hose kit



### Pressure connection

A set of test point adaptors to connect the tool-less quick fit PV624 pressure port or the extension hoses to the device under test

**P/N IO620-BSP:** G1/8 male and G1/4 male, G1/4 female, G3/8 female and G1/2 female

**P/N IO620-NPT:** 1/8" NPT male and 1/4" NPT male, 1/4" NPT female, 3/8" NPT female, and 1/2" NPT female

**P/N IO620-MET:** 14 mm female and 20 mm female

