

# ADT 760

## Automatic Handheld Pressure Calibrator



- Fully automatic calibrator with built-in pump and controller
- Switchable internal pressure modules for expandable ranges
- Accuracy (1 year ) of 0.02% FS
- Less than 4 lbs (1.8 kg) for handheld operation
- Source pressure, measure pressure and electrical
- 4 channels
- Optional HART-communications
- Optional data logging and task documentating
- USB, Wi-Fi and Bluetooth communications

## **Overview**

The Additel 760 series Automatic Handheld Pressure Calibrator takes portable pressure calibration to new levels. Weighing less than 4 lbs (1.8 kg), the ADT760's innovative design contains a built-in pump, precision pressure sensor, internal controller and a large touch-screen color display. To generate pressure, simply key in the desired pressure and the Additel 760 will do the rest. Each unit has four channels: one internal pressure channel for source and measure pressures, two external pressure measurement channels, and one electronic measure and source channel. This series of calibrator has three standard models with the option of adding HART communications, documentation and data logging.

## **Features**

### **ADT760-LLP**

The 760-LLP is designed for low pressure calibration and comes with a built-in pressure module of your choice. The maximum range module compatible with the ADT760-LLP is to  $\pm 30$  inH<sup>2</sup>O ( $\pm 75$  mbar) and provides an accuracy to 0.05% FS (see ordering information for configurations with the option of the ADT760 and a module of your choice). Additional internal pressure modules (ADT155 series) are available and provide a variety of ranges down to  $\pm 0.25$  inH<sup>2</sup>O ( $\pm 0.62$  mbar). The accuracy of 0.05%FS and control stability 0.005%FS is based on the internal module's span. Measurements can be made in gauge or differential mode.

### **ADT760-D**

The 760-D gives you differential and gauge pressure but at a higher pressure range than the ADT760-LLP. Covering the range of -12.5 to 35 psi (-0.86 to 2.5 bar) and with an accuracy of 0.02%FS, the ADT760-D is an ideal solution to cover very common gauge and differential pressure measurements. The Additel 760-D comes with an internal module of your choice. The maximum range module compatible with the ADT760-D is to 35 psi. Lower pressure configurations down to  $\pm 10$  inH<sup>2</sup>O differential can be purchased to improve accuracy at lower pressures.

### **ADT760-MA**

The 760-MA generates and controls pressure from vacuum pressures up to 300 psig (20 bar.g) with an accuracy of 0.02%FS. Equipped with a built-in barometric reference, each unit can switch between gauge and absolute pressure types. A variety of internal sensors are available which offer lower pressure ranges for improved performance.

## **Documenting Process Functionality**

Each model of the Additel 760 series has an option incorporating documentation and communication functions turning your 760 into a multifunction documenting process calibrator. This feature provides HART communication, task documentation and data logging.



## Pressure Specifications

Specification	760-LLP	760-D	760-MA
Max. Pressure Range	±75 mbar (±30 inH <sup>2</sup> O)	-0.86 to 2.5 bar (-12.5 to 35 psi)	-0.86 to 20 bar (-12.5 to 300 psig)
Accuracy (%FS)	±0.05 <sup>[1]</sup>	0.02 <sup>[1]</sup>	0.02 <sup>[1][3]</sup>
Stability (%FS)	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>
Pressure Type	Differential, Gauge	Differential, Gauge	Gauge, Absolute
Over Range Indication	120%		
Resolution	6 digits		
Measurement Units	Pa, hPa, kPa, mPa, bar, mbar, psi, mmHg@0°C, inHg@0°C, inH <sup>2</sup> O@4°C, mmH <sup>2</sup> O@4°C, cmH <sup>2</sup> O@4°C, mH <sup>2</sup> O@4°C, mmH <sup>2</sup> O@20°C, cmH <sup>2</sup> O@20°C, mH <sup>2</sup> O@20°C, inH <sup>2</sup> O@20°C, kg/m <sup>2</sup> , mtorr, torr, lb/ft <sup>2</sup> , tsi, custom		
Barometric Accuracy	N/A	N/A	60 Pa <sup>[4]</sup>
Connection	Barb fitting	Hose, 1.5 m (5 ft), with built-in filter to 1/4BSPF, 1/4NPTF, and M20F adapters	Hose, 1.5 m (5 ft), with built-in filter to 1/4BSPF, 1/4NPTF, and M20F adapters
Pressure Output Rate	<30 seconds (100 ml / 30 inH <sub>2</sub> O)	<10 seconds (5 ml / 35 psi)	<90 seconds (5 ml / 300 psi)

[1] FS specification applies to the span of the module range

[2] Stability based on FS of the internal pressure module. Stability is 0.005%FS or 0.05 pa whichever is greater. Internal module is switchable.

[3] Specification based on gauge measurement. An additional 60 Pa uncertainty will need to be included when measuring in absolute mode.

[4] 60 Pa uncertainty (k=2) includes calibration uncertainty, linearity, and long-term stability (<30 Pa per year). Barometer range of 60 to 110 kPa..

## Electrical Specifications

Specification	Range	Resolution	Accuracy	Note
mA Measure	±30 mA	0.0001 mA	±0.01% RD+0.005%FS	Impedance <10Ω
V Measure	±30 V	0.0001 V	±0.01% RD+0.005%FS	Impedance >1 MΩ
mA Source	24 mA	0.001 mA	±0.01% RD+0.005%FS	20 mA @ 1K
Loop Power Source	24 V	k/A	±1 V	50 mA (Max. Loading)
Pressure Switch	Open, close. Support for mechanical switches and NPN/PNP digital switches			
Temperature Compensation	5°C to 35°C (41°F to 95°F)			
Temperature Coefficient	< ± (0.001% RD + 0.001% FS) /°C outside of 5°C to 35°C.			

## Internal Modules - Specifications and Compatibility

Module	Module Range		Media	Accuracy (%FS) <sup>[1]</sup>	Burst Pressure	760-LLP	760-D	760-MA
	mbar	inH <sub>2</sub> O						
DP025	± 0.62	± 0.25	Gas	± 0.2 <sup>[2]</sup>	100x	•		
DP050	± 1.25	± 0.5	Gas	± 0.1 <sup>[3]</sup>	100x	•		
DP1	± 2.5	± 1	Gas	± 0.05 <sup>[4]</sup>	100x	•		
DP2	± 5	± 2	Gas	± 0.05 <sup>[4]</sup>	100x	•		
DP5	± 10	± 5	Gas	± 0.05 <sup>[4]</sup>	50x	•		
DP10	± 25	± 10	Gas	± 0.05 <sup>[4]</sup>	20x	•	•	
DP20	± 50	± 20	Gas	± 0.05	20x	•	•	
DP30	± 75	± 30	Gas	± 0.05	20x	•	•	
DP50	± 125	± 50	Gas	± 0.05	3x		•	
DP150	± 350	± 150	Gas	± 0.02	3x		•	
DP300	± 700	± 300	Gas	± 0.02	3x		•	
DP400	-860 to 1.000 (-0.86 – 1 bar)	-350 to 400 (-12.5 – 15 psi)	Gas	± 0.02	3x		•	
DP800	-860 to 2.000 (-0.86 – 2 bar)	-350 to 800 (-12.5 – 30 psi)	Gas	± 0.02	3x		•	
DP1K	-860 to 2.500 (-0.86 – 2.5 bar)		Gas	± 0.02	3x		•	
Gauge Pressure	bar	psi						
CP10	± 0.7	± 10	Gas	± 0.02 <sup>[5]</sup>	3x		•	•
CP15	-0.95 to 1	-12.5 to 15	Gas	± 0.02 <sup>[5]</sup>	3x		•	•
CP30	-0.95 to 2	-12.5 to 30	Gas	± 0.02 <sup>[5]</sup>	3x		•	•
CP35	-0.95 to 2.5	-12.5 to 35	Gas	± 0.02 <sup>[5]</sup>	3x		•	•
CP50	-0.86 to 3.5	-12.5 to 50	Gas	± 0.02 <sup>[5]</sup>	3x			•
CP100	-0.95 to 7	-12.5 to 100	Gas	± 0.02 <sup>[5]</sup>	3x			•
CP150	-0.95 to 10	-12.5 to 150	Gas	± 0.02 <sup>[5]</sup>	3x			•
CP200	-0.95 to 14	-12.5 to 200	Gas	± 0.02 <sup>[5]</sup>	3x			•
CP300	-0.95 to 20	-12.5 to 300	Gas	± 0.02 <sup>[5]</sup>	3x			•

[1] FS specification applies to the span of the module range. Accuracy includes one-year stability, except for DP025 to DP10 modules

[2] Accuracy is a 6 months spec, 1-year long-term drift is 0.2% FS.

[3] Accuracy is a 6 months spec, 1-year long-term drift is 0.1% FS.

[4] Accuracy is a 6 months spec, 1-year long-term drift is 0.05% FS.

[5] Specification based on gauge measurement. An additional 60 Pa uncertainty will need to be included when measuring in absolute mode. Applicable only for use with the ADT760-MA.



## General Specifications

Specification	Description
Channels	Four total: one electrical, one internal pressure, two external pressure (measure only)
Enclosure / IP Rating	IP54, water and dust proof
Battery	Rechargeable Li-Ion battery, typically 10 hours of operation, recharges in less than 4 hours
Display	800x480 TFT 5-inch colour touch screen
Communications	USB, WiFi, Bluetooth
Weight	< 1.8 kg (< 4 lbs)
Size	235 x 110 x 70 mm (9.3 x 4.3 x 2.8 in)
Certification	NIST-traceable certificate with data included
HART - Communications	Optional (ADT760-X-DL model)
Data Logging	Optional (ADT760-X-DL model) to 1.000.000 readings (date and time stamped)
Task Documentation	Optional (ADT760-X-DL model) up to 250 tasks
Automation Functions	Switch test, auto step, leak test
Misuse Protection	Up to 30 V on any two sockets
Multi Lingual Interface	English, German, French, Italian, Spanish, Portuguese, Chinese, Japanese and Russian
Pump Life	> 500000 cycles
Power	Rechargeable Li-Ion battery, external power: 110/220V power adapter 10V
Environment Specifications	Operation: 0° C to 50° C (32° F to 122° F), 0-90% RH, less than 3,000 meters Pressure Compensated temperature: 0°C to 50°C (32°F to 122°F) Storage temperature: -20°C to 70°C (-4°F to 158°F)
Vibration and Shock	Vibration: 20 to 2.000 Hz (4g) Shock: 1 meter drop test (8g)
Compliance	CE
Warranty	1 year



## **Optional Internal Pressure Modules**

ADT155-DP025-760	Pressure module for ADT760-LLP, $\pm 0.62$ mbar, 0.2% FS
ADT155-DP050-760	Pressure module for ADT760-LLP, $\pm 1.25$ mbar, 0.1% FS
ADT155-DP1-760	Pressure module for ADT760-LLP, $\pm 2.5$ mbar, 0.05% FS
ADT155-DP2-760	Pressure module for ADT760-LLP, $\pm 5$ mbar, 0.05% FS
ADT155-DP5-760	Pressure module for ADT760-LLP, $\pm 10$ mbar, 0.05% FS
ADT155-DP10-760	Pressure module for ADT760-LLP & -D, $\pm 25$ mbar, 0.05% FS
ADT155-DP20-760	Pressure module for ADT760-LLP & -D, $\pm 50$ mbar, 0.05% FS
ADT155-DP30-760	Pressure module for ADT760-LLP & -D, $\pm 75$ mbar, 0.05% FS
ADT155-DP50-760	Pressure module for ADT760-D, $\pm 160$ mbar, 0.05% FS
ADT155-DP150-760	Pressure module for ADT760-D, $\pm 350$ mbar, 0.02% FS
ADT155-DP300-760	Pressure module for ADT760-D, $\pm 700$ mbar, 0.02% FS
ADT155-DP400-760	Pressure module for ADT760-D, -860 to 1.000 mbar, 0.02% FS
ADT155-DP800-760	Pressure module for ADT760-D, -860 to 2.000 mbar, 0.02% FS
ADT155-DP1K-760	Pressure module for ADT760-D, -860 to 2.500 mbar, 0.02% FS
ADT155-CP10-760	Pressure module for ADT760-D & -MA, $\pm 700$ mbar, 0.02% FS
ADT155-CP15-760	Pressure module for ADT760-D & -MA, -0.86 to 1 bar, 0.02% FS
ADT155-CP30-760	Pressure module for ADT760-D & -MA, -0.86 to 2 bar, 0.02% FS
ADT155-CP35-760	Pressure module for ADT760-D & -MA, -0.86 to 2.5 bar, 0.02% FS
ADT155-CP50-760	Pressure module for ADT760-D & -MA, -0.86 to 3.5 bar, 0.02% FS
ADT155-CP100-760	Pressure module for ADT760-MA, -0.86 to 7 bar, 0.02% FS
ADT155-CP150-760	Pressure module for ADT760-MA, -0.86 to 10 bar, 0.02% FS
ADT155-CP200-760	Pressure module for ADT760-MA, -0.86 to 14 bar, 0.02% FS
ADT155-CP300-760	Pressure module for ADT760-MA, -0.86 to 20 bar, 0.02% FS

## **Ordering Information**

**For all Modell Numbers**






**See Selection Guide**





**Model**

Model Number	Description
ADT760-LLP	Automatic Handheld Pressure Calibrator, 75 mbar
ADT760-LLP-DL	Automatic Handheld Pressure Calibrator, 75 mbar, with HART-and data logging
ADT760-D	Automatic Handheld Pressure Calibrator, -0.86 to 2.5 bar
ADT760-D-DL	Automatic Handheld Pressure Calibrator, -0.86 to 2.5 bar, with HART-and data logging
ADT760-MA	Automatic Handheld Pressure Calibrator, -0.86 to 20 bar
ADT760-MA-DL	Automatic Handheld Pressure Calibrator, -0.86 to 20 bar, with HART- and data logging


**Accessories (included)**

Model	Quantity	Picture
ADT100-760 KIT Adapter set (excl. ADT760-LLP)	1 set (1/4 BSPF to G1/4NPTF to M20F)	
ADT100-760 Hose (excl. ADT760-LLP)	1 pc	
9816-X 110V/220V external power adapter	1 pc	
9724 Chargeable Li-ion battery	1 pc	
9025 Test leads for calibrator	1 set (3 pcs)	
CD-Manual	1 pc	
NIST-traceable certificate	1 pc	DAkKS-Calibration Certificate on demand

**Transport Accessories – Optional**

	Soft carrying case for ADT760, test leads, and many accessories	9913-760-SC
	Carrying case for ADT760 and various accessories	9914-760

## Optional Accessories

Model	Description	Picture
ADT160A	Pressure modules (reference 160A data sheet; module connection cable sold separately)	
9060	Pressure module connection cable	
ADT100-760-N	Special Connector to 1/4 NPT quick connector	
ADT100-760-B	Special Connector to 1/4 BSP quick connector	
ADT100-760-M	Special Connector to M20x1.5 quick connector	
ADT100-760-N2	Special Connector to 1/2NPT quick connector	
ADT100-760-B2	Special Connector to 1/2 BSP quick connector	
ADT128-B	Pneumatic Pressure Manifold for ADT760, -15 to 3000 psi, single port, (1/4 BSP F) G1/4"	
ADT128-B2	Pneumatic Pressure Manifold for ADT760, -15 to 3000 psi, single port, (1/2 BSP F) G1/2"	
ADT128-N	Pneumatic Pressure Manifold for ADT760, -15 to 3000 psi, single port, (1/4 NPT F) G1/4"	
ADT128-N2	Pneumatic Pressure Manifold for ADT760, -15 to 3000 psi, single port (1/2 NPT F) G1/2"	
ADT128-M	Pneumatic Pressure Manifold for ADT760, -15 to 3000 psi, single port, M20x1.5	
9240	DP gauge holder, rubber	
1220211087	Filter, set of 2 pcs	
ADT100-760-CNT	Special connector (to be used to adapt from the ADT760 to ADT100-760-KIT adapters)	



## Selection Guide

Model Features	760-LLP	760-LLP-DL	760-D	760-D-DL	760-MA	760-MA-DL
Pressure Range <sup>[1]</sup>	±75 mbar (± 30 inH <sup>2</sup> O)	±75 mbar (± 30 inH <sup>2</sup> O)	-0.86 to 2.5 bar (1.5 to 35 psi)	-0.86 to 2.5 bar (-12.5 to 35 psi)	-0.86 to 20 bar (-12.5 to 300 psig)	-0.86 to 20 bar (-12.5 to 300 psig)
Accuracy (%FS)	0.05 <sup>[1]</sup>	0.05 <sup>[1]</sup>	0.02 <sup>[1]</sup>	0.02 <sup>[1]</sup>	0.02 <sup>[1][3]</sup>	0.02 <sup>[1][3]</sup>
Stability (%FS)	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>
Gauge Pressure	•	•	•	•	•	•
Differential Pressure	•	•	•	•		
Absolute Pressure					•	•
Barometric Pressure					•	•
Removable Internal Module	•	•	•	•	•	•
External Pressure Module	•	•	•	•	•	•
Temperature-Compensated	•	•	•	•	•	•
Built-in Electrical Pump	•	•	•	•	•	•
Built-in Filter	•	•	•	•	•	•
Built-in Liquid Trap	•	•	•	•	•	•
Source/Simulate 24mA	•	•	•	•	•	•
Measure mA or V	•	•	•	•	•	•
24V	•	•	•	•	•	•
Pressure switch test	•	•	•	•	•	•
HART Communication		•		•		•
Task Documentation		•		•		•
Data Logging		•		•		•
Channels	4	4	4	4	4	4
USB, WiFi, and Bluetooth	•	•	•	•	•	•

[1] FS specification applies to the span of the module range.

[2] Stability based on FS of the internal pressure module. Internal module is switchable.

[3] Specification based on gauge measurement. An additional 60 Pa uncertainty will need to be included when measuring in absolute mode.



# Your Note

A series of horizontal dashed lines for writing notes.