

TestPower IHP140

	IHP140
Test pressure max.	30 bar
Flow rate max.	62 cm ³ /stroke
Plunger-Ø	14 mm
Category	1-stage
Weight	4 kg
Dimensions (L x W x H)	240 x 145 x 610 mm

Light test pump up to 30 bar with drain valve, pressure gauge, 1 m hose line with G $\frac{1}{2}$ A threaded connection at discharge connection.



TestPower IHP140

TestPower IUX60

	IUX60
Test pressure max.	60 bar
Flow rate max.	11 cm ³ /stroke
Plunger-Ø	20 mm
Category	1-stage
Weight	6.5 kg
Dimensions (L x W x H)	500 x 180 x 330 mm

Small, easy to handle test pump up to 60 bar with drain valve, pressure gauge, including 10 l stainless steel tank and 2 m hose line, G $\frac{1}{2}$ A threaded connection at discharge connection.



TestPower IUX60

TestPower IHP 220/300/500

	IHP220	IHP300	IHP500
Test pressure max.	100 bar	60 bar	200 bar
Flow rate max.	15 cm ³ /stroke	28 cm ³ /stroke	79/8 cm ³ /stroke
Plunger-Ø	22 mm	30 mm	50/16 mm
Category	1-stage	1-stage	2-stage
Weight	14 kg	14 kg	18 kg
Dimensions (L x W x H)	438 x 318 x 520 mm	438 x 318 x 520 mm	438 x 318 x 590 mm

Robust, easy to handle test pump up to 200 bar with drain valve, pressure gauge, 30 l oval tank and 3 m hose line. Ideal for testing small volumes. One and two stage version.



TestPower IHP500



TestPower IHP32-8

TestPower IHP32

Two stage hand operated test pump up to 1,000 bar with drain and safety valve, pressure gauge, 60 l mobile rectangular tank and 3 m hose line. Designed for higher pressures, available also in stainless steel design.

	IHP32-12	IHP32-12VA	IHP32-8
Test pressure max.	630 bar	630 bar	1,000 bar
Flow rate max.	28/3.4 cm ³ /stroke	28/3.4 cm ³ /stroke	28/1.5 cm ³ /stroke
Plunger-Ø	32/12 mm	32/12 mm	32/8 mm
Category	2-stage	2-stage	2-stage
Weight	38 kg	51 kg	38kg
Dimensions (LxW xH)	480x330x820 mm	480x330x820 mm	480x330x820 mm



TestPower IHP20-5

TestPower IHP20-5

	IHP20-5
Test pressure max.	3,000 bar
Flow rate max.	11/0.5 cm ³ /stroke
Plunger-Ø	20/4.5 mm
Category	2-stage
Weight	53 kg
Dimensions (LxW xH)	480 x 320 x 989 mm

Two stage hand operated test pump up to 3,000 bar with drain valve, pressure gauge, 60 l mobile rectangular stainless steel tank and 1.5 m hose line with connection M26 x 1.5.