

Overview



SIWAREX WP241 is a flexible weighing module for belt scales. The compact module is easy to install in the SIMATIC S7-1200 automation system. It can also be operated as a stand-alone module, i.e. without a SIMATIC CPU.

Benefits

SIWAREX WP241 offers the following key advantages:

- Uniform design technology and consistent communication in SIMATIC S7-1200
- Uniform configuration with TIA Portal
- Operation without SIMATIC CPU possible
- Direct connection of an operator panel via Ethernet
- Four digital inputs and outputs, one analog output
- Measurement of weight with a high resolution of ± 4 million parts
- Simple adjustment of belt scales using the SIWATOOL V7 program via the Ethernet interface - even without knowledge of SIMATIC
- Replacement of module possible without renewed calibration of the scale
- Use in hazardous area zone 2
- Different calibration methods: With test weights, test chain, automatically or via material batch.
- Specification of belt inclination angle
- 6 totalization memories
- Simulation of speed and belt load for test purposes
- Comprehensive diagnostics functions

Application

SIWAREX WP241 is the optimal solution wherever belt scales are used that demand high accuracy, high user-friendliness, and flexible system integration. The typical applications of the SIWAREX WP241 are determining the current material flow rate, belt load, and belt speed. Furthermore, 6 totalizers are available for evaluating the amount of material conveyed.

Design

SIWAREX WP241 is a compact technology module in the SIMATIC S7-1200, and it allows direct connection to S7-1200 components via a sliding connector. The rail mounting of the 70 mm (2.76 inch) wide weighing module means that it is extremely easy to mount/wire.

The power supply, load cells, RS 485 interface, digital input/outputs and the analog output are connected via the screw plug of the weighing module. An RJ45 plug is used for the Ethernet connection.

Function

The primary task of the SIWAREX WP241 is to measure the speed of the belt, to measure and convert the sensor voltage to a weight value, and to precisely calculate the amount of material conveyed or material flow rate.

The volume of material conveyed can be recorded in 6 totalization memories: The accumulated totalization memory determines the conveyed material over the entire operating time of the scale (can only be reset by loading the factory settings). The overall total and the four remaining totalization memories are available for use as required. For example, for recording the daily or weekly totals.

Four different options are available for rapid commissioning:

- **Automatic calibration**
The calibration is calculated automatically using the load cell parameters entered. Only the zero point has to be calculated at the actual plant.
- **Calibration with calibration weights or test weights**
Test weights are secured to the weighing equipment and the conveyor belt is started. The calibration values are determined while the belt is running. The zero point must also be calculated.
- **Calibration with test chain**
Instead of test weights, a chain of a known weight can be placed on the measuring points of the belt. The calibration values are calculated as for calibration with test weights.
- **Calibration via material batch**
This method can be used if a volume of material is available, but neither test weights nor a chain are available. The material can either be preweighed or weighed afterwards. It is conveyed over the belt scale. Then the weighing module calculates the calibration characteristic automatically.

If "Automatic set to zero" is active, the electronic weighing system automatically executes a "set to zero" procedure when the belt reaches the "set to zero" area.

Weighing Electronics

SIWAREX weighing electronics for SIMATIC

Belt scales

SIWAREX WP241

Function (continued)

Extensive diagnostics functions are available. Diagnostic messages are output to the different interfaces. In simulation mode, both the speed and the belt load can be specified by the user. This makes it possible to test many functions in advance without operating belt scales. Both the digital inputs/outputs and the analog output can also be simulated for test purposes. The "Trace" function is extremely helpful for optimizing the plant or when troubleshooting. It records the weighing history stored in the internal module memory (e.g. material flow rate, belt load, speed) and exports it to Excel in a graphical format.

Monitoring the scale signals and states

The SIWAREX WP241 monitors the belt load, the material flow rate, and the belt speed, and it signals if the limits are exceeded. The respective limits can be parameterized as required.

Consistent and uniform communication between all system components enables fast, reliable and cost-effective integration and diagnosis in industrial processes.

Integration in the plant environment

SIWAREX WP241 can be directly integrated into the SIMATIC S7-1200 via the SIMATIC bus. Standalone operation without SIMATIC is also possible.

A wide variety of connection options are provided via the RS 485 and Ethernet interface. Via Modbus TCP/IP or Modbus RTU, control panels can be connected and it is also possible to communicate with various automation systems. A PC for programming the SIWAREX WP241 via SIWATOOL can be connected to the Ethernet interface.

SIWAREX WP241 can be integrated into the system software using all standard PLC programming languages from the TIA Portal. In contrast to serially linked electronic weighing systems, SIWAREX WP241 does not need costly additional modules to link it to SIMATIC.

Used in conjunction with SIWAREX WP241, it is possible to configure freely programmable, modular weighing systems in SIMATIC, which can be adapted to company-specific requirements as needed.


In addition to the configuration package, fully-featured SIWAREX WP241 "Ready for use" software is also available free-of-charge. It shows beginners how to integrate the module in a STEP 7 program and offers a basis for application programming. This allows you to connect the scale to an operator panel either connected to the SIMATIC CPU or connected directly to the SIWAREX WP241.

Software

There is also the option of using a Windows PC for commissioning and servicing. The program SIWATOOL enables the belt scales to be set without prior knowledge of the automation system, as required. During servicing, the technician can use a PC to quickly and simply analyze and test the procedures in the scale.

The following are just some of the tasks that can be carried out using SIWATOOL V7:

- Parameterization and calibration of the scale
- Testing/Simulation of scale properties
- Recording, analysis and export of scale traces ("Trace")
- Creation of backup files for rapidly replacing modules without calibration




SIWAREX WP241 SIWATOOL

It is also extremely helpful to analyze the diagnostics buffer which can be saved together with the parameters following reading out from the module.

The SIWAREX WP241 weighing module includes a trace mode for optimization of weighing sequences. The recorded weight values and associated states can be displayed as trends using SIWATOOL V7 and MS Excel.

Upgrading firmware

An additional program function can be used to download a new firmware version onto the SIWAREX WP241 on site. This means that firmware upgrades can be carried out on site as required anywhere in the world.



SIWAREX WP241 "Ready for use"

Technical specifications

SIWAREX WP241	
Integration in automation systems	
S7-1200	SIMATIC S7-1200 system bus
Operator panel and/or automation systems from other vendors	Via Ethernet (Modbus TCP/IP) or RS 485 (Modbus RTU)
Communication interfaces	<ul style="list-style-type: none"> • SIMATIC S7-1200 backplane bus • RS 485 (Modbus RTU) • Ethernet (SIWATOOL V7, Modbus TCP/IP) • Analog output 0/4 - 20 mA • 4 × digital outputs, 24 V DC, floating, short-circuit proof • 4 × digital inputs 24 V DC, floating
Commissioning options	<ul style="list-style-type: none"> • Using SIWATOOL V7 • Using function block in SIMATIC S7-1200 CPU / Touch Panel • Using Modbus TCP/IP • Using Modbus RTU
Measuring accuracy	
Error limit according to DIN 1319-1 of full-scale value at 20 °C ± 10 K (68 °F ± 10 K)	0.05%
Internal resolution	Up to ± 4 million parts
Measuring frequency	100 / 120 Hz
Digital filter	Separate, variable adjustable low-pass and average filter for loading and speed
Filter for conveyor load	Low-pass filter (limit frequency 0.05 ... 50 Hz)
Filter for belt speed	Low-pass filter (limit frequency 0.05 ... 50 Hz)
Weighing functions	
Readout data	<ul style="list-style-type: none"> • Weight • Belt load • Material flow rate • Accumulated total • Main total • Free totals 1 ... 4 • Belt speed
Limits (min/max)	<ul style="list-style-type: none"> • Belt load • Material flow rate • Belt speed
Load cells	Full-bridge strain gauges in 4-wire or 6-wire system

SIWAREX WP241	
Load cell powering	
Supply voltage (regulated via feedback)	4.85 V DC
Permissible load resistance	<ul style="list-style-type: none"> • R_{Lmin} > 40 Ω • R_{Lmax} < 4 100 Ω
With SIWAREX IS Ex interface	<ul style="list-style-type: none"> • R_{Lmin} > 50 Ω • R_{Lmax} < 4 100 Ω
Load cell characteristic	1 ... 4 mV/V
Permissible measurement signal range	-21.3 ... +21.3 mV
Max. distance of load cells	500 m (229.66 ft)
Connection to load cells in Ex zone 1	Optionally via SIWAREX IS Ex interface (compatibility of the load cells must be checked)
Approvals/certificates	<ul style="list-style-type: none"> • ATEX Zone 2 • UL • EAC • KCC • RCM
Auxiliary power supply	
Rated voltage	24 V DC
Max. power consumption	200 mA
Max. power consumption SIMATIC Bus	3 mA
IP degree of protection to DIN EN 60529; IEC 60529	IP20
Climatic requirements	
$T_{min(IND)}$... $T_{max(IND)}$ (operating temperature)	
• Vertical installation	-10 ... +40 °C (14 ... 104 °F)
• Horizontal installation	-10 ... +55 °C (14 ... 131 °F)
EMC requirements	According to EN 45501
Dimensions	70 × 75 × 100 mm (2.76 × 2.95 × 3.94 inch)

Weighing Electronics

SIWAREX weighing electronics for SIMATIC

Belt scales

SIWAREX WP241

Selection and ordering data

SIWAREX WP241 weighing module

Single-channel, legal-for-trade, for automatic proportioning and filling scales (GFI, CWI, NAWI) with analog load cells / full-bridge strain gauge (1 - 4 mV/V), 1 × LC, 4 × DQ, 4 × DI, 1 × AQ, 1 × RS 485, Ethernet port.

SIWAREX S7-1200 Equipment Manual

Available in a range of languages
Free download on the Internet at:

<http://www.siemens.com/weighing/documentation>

SIWAREX WP241 "Ready for use"

Complete software package for belt scale (for S7-1200 and a directly connected operator panel)

Free download on the Internet at:

<http://www.siemens.com/weighing/documentation>

SIWATOOL V4 & V7

Service and commissioning software for SIWAREX weighing modules

Ethernet cable patch cord 2 m (7 ft)

For connecting SIWAREX WP241 to a PC (SIWATOOL), SIMATIC CPU, panel, etc.

Accessories

SIWAREX JB junction box, aluminum housing

For connecting up to 4 load cells in parallel, and for connecting multiple junction boxes.

SIWAREX JB junction box, stainless steel housing

For connecting up to 4 load cells in parallel.

SIWAREX JB junction box, stainless steel housing (ATEX)

For parallel connection of up to 4 load cells (for zone allocation, see manual or type-examination certificate).

SIWAREX IS Ex interface

For intrinsically-safe connection of load cells. With ATEX approval (not UL/FM). Suitable for SIWAREX electronic weighing systems. Compatibility of load cells must be checked separately.

- Short-circuit current < 199 mA DC
- Short-circuit current < 137 mA DC

7MH4960-4AA01

7MH4900-1AK01

6XV1850-2GH20

7MH5001-0AA20

7MH5001-0AA00

7MH5001-0AA01

7MH4710-5BA

7MH4710-5CA

Article No.

Cable (optional)

Cable Li2Y 1 × 2 × 0.75 ST + 2 × (2 × 0.34 ST) – CY

For connecting SIWAREX electronic weighing systems to junction box (JB), extension box (EB) and Ex interface or between two EBs. For permanent installation. Occasional bending is possible.

External diameter:
approx. 10.8 mm (0.43 inch)

Permissible ambient temperature
-40 ... +80 °C (-40 ... +176 °F)

Sold by the meter.

- Sheath color: orange
- For hazardous atmospheres. Sheath color: blue.

7MH4702-8AG
7MH4702-8AF

Ground terminal for connecting the load cell cable shield to the grounded DIN rail

6ES5728-8MA11

Commissioning

Commissioning charge for one belt scale with SIWAREX module

(Flat charge for travel and setup must be ordered separately)

Scope:

- Recording of data
- Checking of mechanical installation of the scale
- Checking of electrical wiring and function
- Dynamic adjustment of the scale

Requirements:

- Mechanical design functional
- Modules electrically wired and tested
- Calibration weights available
- Free access to scale

9LA1110-8SM50-0AA0

Flat charge for travel and setup in Germany

9LA1110-8RA10-0AA0