

Stainless steel platform scale KERN SFB-H · SFB



Stainless steel platform scales with IP65/67 protection, also with XL platform or EC type approval [M]

Features

- **Ideal for the robust industrial applications**
- **1 Platform:** made entirely of stainless steel, silicone-coated stainless steel load cell, protection against dust and water splashes IP67
- **2 Display device:** stainless steel, protection against dust and water splashes IP65, (only when using rechargeable battery pack)

- **3 SFB-H: Column,** standard, for models with weighing plate size 300x240 mm: Column height approx. 200 mm
400x300 mm: Column height approx. 200 mm

Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 3 m

- Rechargeable battery pack internal, operating time up to 35 h without backlight, charging time approx. 12 h
- Permissible ambient temperature -10 °C/40 °C

Accessories

- **Data interface RS-232,** interface cable included, approx. 1,5 m, must be ordered at purchase, KERN KFN-A01
- **Stand** to be screwed onto the platform, height of stand approx. 600 mm, KERN SFB-A01
- **4 Stand** to elevate display device, height of stand approx. 800 mm, **Stand** to elevate display device, height of stand approx. 800 mm, KERN BFS-A07
- Further details, plenty of further accessories and suitable printers see *Accessories*


STANDARD



OPTION




















FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Net weight approx. kg	Weighing plate WxD	Option				
							Verification		DAkkS Calibr. Certificate		
							MDD KERN		DAkkS KERN		
KERN											
SFB 50K-3XL	50	5	-	-	14	500x400	-		963-128		
SFB 100K-2L	100	10	-	-	14	500x400	-		963-129		
SFB 100K-2XL	100	10	-	-	26	650x500	-		963-129		
SFB 200K-2XL	200	20	-	-	26	650x500	-		963-129		
with elevated display											
SFB 10K1HIP	10	1	-	-	8	300x240	-		963-128		
SFB 20K2HIP	20	2	2	-	8	300x240	-		963-128		
SFB 50K5HIP	50	5	5	-	8	300x240	-		963-128		
SFB 50K5LHIP	50	5	5	-	8	400x300	-		963-128		
SFB 100K10HIP	100	10	-	-	14	400x300	-		963-129		
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.											
SFB 60K-2XLM	60	20	20	400	16	500x400	965-229		963-129		
SFB 100K-2XLM	150	50	50	1000	24	650x500	965-229		963-129		
SFB 300K-1LM *	300	100	100	2000	26	650x500	965-229		963-129		
with elevated display											
SFB 15K5HIPM	15	5	5	100	8	300x240	965-228		963-128		
SFB 30K10HIPM	30	10	10	200	8	300x240	965-228		963-128		
SFB 60K20LHIPM	60	20	20	400	14	400x300	965-229		963-129		
SFB 100K-2HM	150	50	50	1000	13	400x300	965-229		963-129		

Pictograms

	Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)		KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems		Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.
	Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required		GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection		Stainless steel: The balance is protected against corrosion
	Easy Touch: Suitable for the connection, data transmission and control through PC, tablet or smartphone		GLP/ISO log: With weight, date and time. Only with KERN printers		Suspended weighing: Load support with hook on the underside of the balance
	Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.		Piece counting: Reference quantities selectable. Display can be switched from piece to weight		Battery operation: Ready for battery operation. The battery type is specified for each device
	Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.		GLP/ISO log: With weight, date and time. Only with KERN printers		Rechargeable battery pack: Rechargeable set
	Data interface RS-232: To connect the balance to a printer, PC or network		Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out		Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
	RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible		Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display		Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
	USB data interface: To connect the balance to a printer, PC or other peripherals		Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition		Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
	Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals		Totalising level A: The weights of similar items can be added together and the total can be printed out		Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
	WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals		Percentage determination: Determining the deviation in % from the target value (100 %)		Weighing principle: Tuning fork: A resonating body is electromagnetically excited, causing it to oscillate
	Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.		Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details		Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
	Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements		Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model		Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
	Interface for second balance: For direct connection of a second balance		Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value		Verification possible: The time required for verification is specified in the pictogram
	Network interface: For connecting the scale to an Ethernet network				DAkKs calibration possible: The time required for DAkKs calibration is shown in days in the pictogram
	Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module				Package shipment: The time required for internal shipping preparations is shown in days in the pictogram

*The *Bluetooth*® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkKs calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkKs calibration laboratory today is one of the most modern and best-equipped DAkKs calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkKs calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkKs calibration of balances with a maximum load of up to 50 t
- DAkKs calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkKs calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

ICS Schneider Messtechnik GmbH
Briesestraße 59
D-16562 Hohen Neuendorf / OT Bergfelde

Tel.: 03303 / 50 40 66

Fax: 03303 / 50 40 68

info@ics-schneider.de
www.ics-schneider.de

