SCHNEIDER MESSTECHNIK

Product Data Sheet Leica DISTO™ D1

Features



Range up to 40 m

- ± 2 mm accuracy, 0.1 mm resolution
- X-range Power Technology
- Illuminated display
- Up to 10'000 measurements with 2 x AAA batteries
- Bluetooth® Technology for error-free data transfer
- Works with DISTO[™] Plan App (iOS and Android) and DISTO[™] transfer (Windows)

Technical data

	Leica DISTO™ D1	
Accuracy with favourable conditions *	2.0 mm / 0.08 in ***	
Accuracy with unfavourable conditions **	3 mm / 1/8" ***	
Range with favourable conditions *	0.2 - 40 m / 0.6 - 120 ft ***	
Range with unfavourable conditions **	0.2 - 30 m / 0.6 - 100 ft ***	
Smallest unit displayed	0.1 mm / 1/32 in	
X-Range Power Technology	yes	
Laser class	2	
Laser type	635 nm, <1 mW	
ø laser point at distances	6 / 30 / 60 mm 10 / 50 / 100 m	
Protection class	IP54 (dust- and splash water protected)	
Auto. laser switch off after	90 s	
Auto. power switch off after	180 s	
Bluetooth® Smart	Bluetooth® v4.0	
Range of Bluetooth® Smart	up to 10 m	
Battery durability (2 x AAA)	up to 10'000 measurements	
Battery Gulability (2 X AAA)	up to 20 hours operation time	
Dimension (H x D x W)	115 x 43.5 x 23.5 mm 4.53 x 1.71 x 0.93 in	
Weight (with batteries)	87 g/ 3.07 oz	
Temperature range Storage Operation	-25 to 70°C / -13 to 158°F 0 to 40°C / 32 to 104°F	

* favourable conditions: white and diffuse reflecting target (white painted wall), low background illumination and moderate temperatures.

** unfavourable conditions: targets with lower or higher reflectivity or high background illumination or temperatures at the upper or lower end of the specified temperature range.

*** Tolerances apply from 0.05 m to 5 m with a confidence level of 95%. Above 5 m the tolerance may deteriorate according to the values given in the manual of the unit.

Functions

Distance measuring	Permanent measuring	Веер
Illuminated display	Bluetooth® Smart	



- when it has to be **right**



Tel.: 03303 / 50 40 66 Fax.: 03303 / 50 40 68

Scope of Delivery



Leica DISTO™ D1 Art. No. 843418 Art. No. 846805 for U.S. Art. No. 846806 for Japan

Leica DISTO^m D1, 2 x AAA batteries, Calibration Certificate Silver, quick start guide

Accessory

GZM27 stick-on target plate 147 x 98 mm	Art. No. 723774
GLB 30 laser glasses 3 in 1	Art. No. 780117
GLB 10R laser glasses	Art. No. 834534
UC 20 universal charger incl. rechargeable batteries	Art. No. 788956

Extended Warranty



Register your product within 8 weeks of purchase at <u>www.disto.com/warranty</u> and benefit from our 3-year warranty.



in accordance with IEC 60825-1

lllustrations, descriptions and technical specifications are subject to change without prior notice. (V 1.0) Copyright© Leica Geosystems AG, Heerbrugg, Switzerland, 2022.

Leica Geosystems AG Heerbrugg, Switzerland www.leica-geosystems.com



- when it has to be **right**

ICS Schneider Messtechnik GmbH Briesestraße 59 D-16562 Hohen Neuendorf / OT Bergfelde Tel.: 03303 / 50 40 66 Fax.: 03303 / 50 40 68