

DOSE RATE METER

GRAETZ GammaTwin

Product features

- ▲ Small and handy, PTB¹⁾ approved dose rate meter for the measurement of gamma radiation and X-rays for ambient dose rate equivalent $H^*(10)$ and ambient dose equivalent $H^*(10)$ (local dose)²⁾
- ▲ Detector: energy compensated GM tube
- ▲ Large, digital indication of measured values on LC display (backlit)
- ▲ Selectable simultaneous or separate indication of dose and dose rate, additionally analog indication of dose rate (logarithmic bargraph)
- ▲ 4 preset dose and dose rate alarm thresholds; upon request GRAETZ changes the standard alarm thresholds according to customer requirements
- ▲ Switchable acoustic single-pulse indication
- ▲ Automatic and continuous storage of the dose into a non-volatile memory
- ▲ Storage of the dose and of set parameters even at battery change
- ▲ Permanent self test
- ▲ Designed for rough use, housing made of aluminium, protection class IP54 (splash proof)
- ▲ Menu-driven user navigation
- ▲ Supplied with a robust nylon bag



¹⁾ Physikalisch-Technische Bundesanstalt, Braunschweig

²⁾ Detecting the personal dose requires a measuring instrument with the measurand $H_p(10)$.

Technical Data	
Dose rate indication range:	0 nSv/h – 70 mSv/h
Dose rate measuring range:	0.5 µSv/h – 70 mSv/h
Dose indication range:	0 nSv – 1.0 Sv
Dose measuring range:	0.5 µSv – 1.0 Sv
Energy range:	45 keV – 1.3 MeV
Dose rate alarm thresholds:	7.5 µSv/h, 25 µSv/h, 40 µSv/h, 300 µSv/h
Dose alarm threshold:	200 µSv, 500 µSv, 1 mSv, 2 mSv
Temperature range:	-20°C up to +60°C
Dimensions:	approx. 26 x 66 x 103 mm
Weight:	approx. 200 g (with batteries)
Power supply:	2 batteries 1.5 V (type AAA)
Acoustic alarm:	approx. 80 dB(A) measured in 30 cm distance
PTB Approval No.:	23.51/10.02

Special version

GammaTwin S with connection facility for external pulse probes (such as the high-sensitive NaI-scintillation probe 2002 or the large-area probe ABG170)