

UNOIQ

Personal, Rechargeable and Modular Single-Gas Monitor

A single-gas detector with extended battery life, modular sensors, and seamless connectivity for enhanced safety.



UnoIQ is a rugged, reliable and compact single-gas detector, built to perform even in the toughest environments. With a long-lasting rechargeable battery, modular sensor technology, and seamless connectivity to Crowcon Connect via Bluetooth®, UnoIQ simplifies asset management while maximising safety and compliance.

FEATURES & BENEFITS

Modular, serviceable sensor trays

Easily swap out pre-calibrated sensor trays without manufacturer intervention, reducing downtime and maintenance costs. Additionally, the plug-and-play design provides flexibility to target different gases.

Extended battery life

UnoIQ delivers up to one-month of use based on standard 8-hour shifts*. Between-shift charging keeps devices operational, with full recharge achieved in under 3 hours.

Seamless hub integration

'Dock and go' functionality with IQhub allows for automated bump testing (<10 seconds), calibration (<30 seconds), and compliance reporting.

Upgradeable to dual-gas detection

The only single-gas detector that can be upgraded to support two gases mid-life, offering flexibility as operational needs evolve.

Comprehensive sensor technologies

The only single-gas detector with every major sensor technology, including, pellistor, electrochemical, and infrared (IR) sensors.

Flexible data upload & connectivity

Options to upload data at multiple touchpoints to Crowcon Connect via Bluetooth® and Near Field Communication (NFC), enabling comprehensive compliance tracking. Advanced analytics provide insights to improve safety, compliance, culture, and performance.

Lightweight, compact design

With its compact design, UnoIQ delivers reliable performance in a lightweight form - measuring under 10cm in height and weighing only 134.2g**, ensuring portability and ease of use.

One button for multiple functions

Single-button operation simplifies the user experience with quick, intuitive control, reducing complexity and learning curves, while making the device more widely accessible.

Durable & reliable

Designed to withstand harsh environments, UnoIQ features robust ingress protection, minimising false readings and enhancing longevity.

Lower total cost of ownership

Achieve up to 30% savings over three years compared to other 2-year serviceable and disposable single-gas models on the market.



SPECIFICATIONS

DEVICE SPECIFICATIONS		GASES & RANGES		
SIZE	Standard: 96 x 55 x 32 mm Deep tray: 106 x 55 x 32 mm	GAS	RANGE	RESOLUTION
WEIGHT**	134.2g (Weight may vary depending on configuration)	Ammonia	0-100ppm	0.1ppm
DURABILITY	6m drop test	Butane	0-100% LEL	1% LEL
RESPONSE TIME (T90)	<10s (sensor dependent)	Carbon Dioxide (Non-IS)	0-2% volume	0.01% volume
ALARMS	Visual, vibrating, audible (95dB), low/high, TWA, STEL	Carbon Monoxide	0-250ppm	1ppm
DISPLAY	Backlit segment display	Chlorine	0-10ppm	0.1ppm
DATA LOGGING	Up to 500 event logs	Hydrogen Sulfide	0-100ppm	0.1ppm
POWER & BATTERY*	Toxics and O2: 10 days continuous (31 days at 8 hour shifts) IR: 1 day continuous (4 days at 8 hour shifts) Pellistor: 1 day continuous (3 days at 8 hour shifts) Recharge time: 0-80% 2 hours 0-100% <3 hours	Methane	0-100% LEL	1% LEL
SAMPLING	None	Nitrogen Dioxide	0-20ppm	0.1ppm
OPERATING TEMPERATURE RANGE	-20 to +55°C / -4 to +131°F	Oxygen	0-25% volume	0.1% volume
HUMIDITY	0-95% RH	Ozone	0-1ppm	0.1ppm
INGRESS PROTECTION	IP66 & IP68	Sulphur Dioxide	0-20ppm	0.1ppm
APPROVALS	CSA US: Class I, Division 1, Groups A, B, C, D T4* ATEX: Ex II 1G Ex ia IIC T4 Ga IECEX: Ex ia da IIC T4 Ga INMETRO: Ex ia IIC T4 Ga* RED/FCC/IC: Wireless *Pending			
CALIBRATION & MAINTENANCE	Automatic bump tests (<10 seconds) and calibrations (<30 seconds) through IQhub; Manual bump and calibrations through device and PC software			
ACCESSORIES	Power cable (device to USB-A & USB-C); Flow plate; IQhub			
CONNECTIVITY	NFC & Bluetooth® (optional) required for connection to Crowcon Connect App			
CROWCON CONNECT	Cloud-hosted web application for safety monitoring and asset management, offering real-time alarms, compliance dashboards, location tracking, device configurations, and essential reporting			
SENSORS	Electrochemical, IR, Pellistor, and Long life O ₂			
LANGUAGES	English			
WARRANTY	2 years (sensor warranty separate)			

ICS Schneider Messtechnik GmbH
Briesestraße 59
D-16562 Hohen Neuendorf / OT Bergfelde

Tel.: 03303 / 50 40 66
Fax.: 03303 / 50 40 68

info@ics-schneider.de
www.ics-schneider.de

Disclaimer

Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This document is not intended to form the basis of a contract.

For more information:

t: +44 (0)1235 557700
e: info@crowcon.com
w: www.crowcon.com

Locate your Regional Sales Representative at:
www.crowcon.com/contact-us/where-to-buy

© 2026 Crowcon Detection Instruments Ltd.

 **crowcon**
DETECTING GAS. SAVING LIVES.